



RAILGATE SERIES - HIGH-CYCLE MODELS WITH BI-FOLD PLATFORMS



☆ 2500 & 3000 LBS CAPACITY

BI-FOLD RAILGATE MODELS

The most versatile, dependable liftgates ever seen in a loading bay, Bi-Fold, High-Cycle models support large steel platforms and high lifting capacities while still remaining completely dock-compatible. The platform drop-down function allows work vehicles to load and unload in any manner at any location.

TKT-80-30 EA60

In the drop-away position, Bi-Fold Railgate platforms rest at bed height, allowing seamless dock compatibility.

The Low-Profile Control, a standard feature on all Tommy Gate Railgate models, includes an inactivity shut-off to guard against unauthorized use.





BI-FOLD RAILGATE FEATURES


- A SAFETY TRIP BAR disengages the lift when an object is detected between the rising platform and the liftgate mainframe
- **B LOW-PROFILE CONTROL** reduced size simplifies operation
- **© SELF-CLOSE ARM** cam-arm system opens/ closes the platform automatically

TWO-YEAR STANDARD WARRANTY

BI-FOLD, HIGH-CYCLE MODELS FOR 96- & 102-INCH WIDE BODIES¹

	Model Number	Body	Load Area	Taper ²	Bed Heights ³	Gate Weight
	<u>Treadplate Platforms</u>					
ity.	89-25 BF TP60	96	83 x 60	13	34 - 54	1320
2500 lb. Capacity	89-25 BF TP70	96	83 x 70	13	38 - 54	1378
25 Ca _l	95-25 BF TP60	102	89 x 60	13	34 - 54	1362
	95-25 BF TP70	102	89 x 70	13	38 - 54	1420
	Treadplate Platforms					
d ≥	89-30 BF TP60	96	83 x 60	13	34 - 54	1320
를 를						
00 pa	89-30 BF TP70	96	83 x 70	13	38 - 54	1378
3000 lb. Capacity	95-30 BF TP60	102	89 x 60	13	34 - 54	1362
	95-30 BF TP70	102	89 x 70	13	38 - 54	1420

BI-FOLD, HIGH-CYCLE RAILGATE DIMENSIONS



IMPORTANT

High-cycle railgate models are intended for use on medium-duty trucks only.

- Bi-Fold, High-Cycle configurations for additional body widths may be available. Contact factory for details.
- 2. Standard, aluminum retention ramp serves as 13-inch, folding, platform taper on Bi-Fold Railgate models.
- 3. Minimum bed heights (laden), Maximum bed heights (unladen).



2500 & 3000 LBS CAPACITY



RAILGATE SERIES - HIGH-CYCLE MODELS WITH FIXED PLATFORMS

HIGH-CYCLE RAILGATE MODELS

High-cycle models apply a steel roller and leafchain pulley system to maximize smoothness of motion, endurance, and strength. This mediumduty railgate is ideal for high-cycle applications in any environment. These lifts are built with the highest quality components and place a priority on function and safety.

89-30 EA55

on

High-cycle railgates come standard with safety trip bar, auto open and close, and recessed lights. Taperintegrated cart stops are optional on extruded-aluminum platform models.







ROLLERS

Steel rollers guide the platform vertically within the rail track and are designed to withstand intensive cycling. Dual-sealed, maintenance-free ball bearings ensure the rollers are long-lasting and perform consistently in all climate conditions.





HIGH-CYCLE MODELS FOR 96" WIDE BODIES1

TWO-YEAR STANDARD WARRANTY

	Model Number	Body	Load Area	Taper	Bed Heights	Gate Weight
	<u>Treadplate Platforms</u>					
	89-25 TP36	96	89 x 36	12	32 - 54	1040
.; ≥	89-25 TP42	96	89 x 42	12	32 - 54	1094
o k	89-25 TP48	96	89 x 48	12	32 - 54	1147
2500 lb. Capacity	Aluminum Platforms 1					
0.0	89-25 EA55	96	89 x 55	12	32 - 54	968
	Gas Bottle Rack Platforms					
	89-25 GBR	96	82 x 30	12	38 - 54	1050
	Treadplate Platforms					
	89-30 TP36	96	89 x 36	12	32 - 54	1040
ح نے	89-30 TP42	96	89 x 42	12	32 - 54	1094
o la	89-30 TP48	96	89 x 48	12	32 - 54	1147
3000 lb. Capacity	Aluminum Platforms ¹					
мÜ	89-30 EA55	96	89 x 55	12	32 - 54	968
	Gas Bottle Rack Platforms					
	89-30 GBR	96	82 x 30	12	38 - 54	1050

ADDITIONAL BODY SIZES


Body Size	Model	Load Width
90"	85	85
102"	95	95


IMPORTANT

High-cycle railgate models are intended for use on medium-duty trucks only.

- 1. See additional aluminum platform depths on page 31.
- 2. For detailed dimensions, visit www.tommygate.com

HIGH-CYCLE RAILGATE DIMENSIONS 2





FIXED

STANDARD FEATURES BI-FOLD PLATFORM MODELS MODELS

0200	Steel Rollers	•	•
	Safety Trip Bar	•	•
	Self-close System	•	•
W.	Recessed Lights	•	•
	Low-profile Control	•	•
	13" Retention Ramp	•	-

- Standard
- Optional
- Not Available

AVAILABLE OPTIONS

	FIXED
BI-FOLD	PLATFORM
MODELS	MODELS

	Above Bed Travel	•	•
MATE CATE OF THE PARTY OF THE P	Recessed LED Lights	•	•
	Dual Controls (w/ pendant)	•	•
	Split Cart Stops	-	•
NO IMAGE	In-cab Shut Off	•	•
	Auxiliary Battery Box	•	•

GAS-BOTTLE RACK PLATFORM

High-Cycle Gas Bottle Rack models incorporate the "High-Cycle" drive system and feature folding, gas bottle rack platforms. Ideal for gas cylinder transporters, these liftgates support higher lifting capacities and feature a platform dropdown function allowing work vehicles to load and unload in any manner at any location.





PLATFORM MATERIALS

FIXED BI-FOLD PLATFORM Models models





RETENTION RAMP

Bi-Fold, High-Cycle models come standard with a 13" tapered, retention ramp.

ALUMINUM PLATFORM DEPTHS

Extruded aluminum platforms (on fixed platform models) are available in any depth, 35" – 70", in 5" increments. Platforms are comprised of interlocking extrusions of 6061-T6 aircraft-quality aluminum.





ramp closes for storage



ramp locks at 90-degrees for cart retention



extended ramp hangs beyond platform level for smooth ground every time

SPLIT CART STOPS

All railgate models with Extruded Aluminum platforms are available with taper-integrated, foot-activated, dual cart stops.







RAILGATE SERIES - STANDARD MODELS WITH DOCK-FRIENDLY PLATFORMS



♦ 1600 & 2000 LBS CAPACITY

DOCK-FRIENDLY RAILGATE MODELS

Dock-friendly models feature folding RF platforms able to achieve non-obstructing positions for forklift or dock loading. Also included are a closure-assist torsion bar and maintenance-free bushings, making them some of the best liftgates ever seen in a loading bay.

89-20 RF 45-12

Dock-friendly platforms fold and can be lowered in the vertical position to allow for easy dock or forklift loading.







PLATFORM DESCRIPTIONS

RF 45-6 Two-piece Extruded Aluminum w/ 45" loading depth (15" flipper) + 6" taper (30" base height)

RF 45-12 Two-piece Extruded Aluminum w/ 45" loading depth (10" flipper) + 12" taper (35" base height)

RF 50-6 Two-piece Extruded Aluminum w/ 50" loading depth (15" flipper) + 6" taper (35" base height)

DOCK-FRIENDLY, STEEL-FRAME MODELS FOR 96" WIDE BODIES

ONE-YEAR STANDARD WARRANTY

	Model Number	Load Area	Taper	Travel	Gate Weight
	Folding Aluminum Platforms				
1600 lb. Capacity	89-16 RF 45-6	89 x 45	6	32 - 52	674
50C apa	89-16 RF 45-12	89 x 45	12	32 - 52	688
- C	89-16 RF 50-6	89 x 50	6	32 - 52	695
d ≥	Folding Aluminum Platforms				
	89-20 RF 45-6	89 x 45	6	32 - 52	674
2000 lb. Capacity	89-20 RF 45-12	89 x 45	12	32 - 52	688
70	89-20 RF 50-6	89 x 50	6	32 - 52	695

DOCK-FRIENDLY, ALUMINUM-FRAME MODELS FOR 96" WIDE BODIES 1


	Model Number	Load Area	Taper	Travel	Gate Weight
. >	Folding Aluminum Platforms				
1600 lb. Capacity	A85-16 RF 45-6	85 x 45	6	32 - 52	539
60(apa	A85-16 RF 45-12	85 x 45	12	32 - 52	553
- O	A85-16 RF 50-6	85 x 50	6	32 - 52	559
.; ≥	Folding Aluminum Platforms				
o it	A85-20 RF 45-6	85 x 45	6	32 - 52	539
2000 lb. Capacity	A85-20 RF 45-12	85 x 45	12	32 - 52	553
7	A85-20 RF 50-6	85 x 50	6	32 - 52	559

ADDITIONAL BODY SIZES

Body Size	Model	Load Width
90"	85	85
102"	95	95

- Aluminum-Frame "Dock-Friendly"
 Railgate models are sized down due to
 the accompanying bolt-on mounting
 flanges. Contact factory for more details.
- 2. For detailed dimensions, visit www.tommygate.com

DOCK-FRIENDLY RAILGATE DIMENSIONS 2







RAILGATE SERIES - STANDARD MODELS WITH FIXED PLATFORMS

STANDARD RAILGATE MODELS


The Tommy Gate Railgate Series consists of expertly-engineered lifts that allow for higher weight capacities and deeper platform loading areas. Standard model railgates employ a padded-slider system and are offered in both steel and aluminum frames.



89-20 EA55

1600 and 2000 lb. capacity railgates come standard with safety trip bar, auto close, and recessed lights.

(Optional LED light kit shown)



ABOVE-BED OPTIONAL CAPABILITY

On standard models, optional above-bed capability allows the platform to rise above the liftgate mainframe for dock loading.





STANDARD, STEEL-FRAME MODELS FOR 96" WIDE BODIES

ONE-YEAR STANDARD WARRANTY

	Model Number	Load Area	Taper	Travel	Gate Weight
	To adulate Distference				
.:≥	Treadplate Platforms 89-16 TP37	89 x 37	6	32 - 54	810
1600 lb. Capacity	89-16 TP42	89 x 42	6	32 - 54 32 - 54	860
160 Cap	Aluminum Platforms 1	22.1.12			
	89-16 EA55	89 x 55	12	32 - 54	715
	T. I.I. Blue				
	Treadplate Platforms	00 v 77	6	70 54	010
2000 lb. Capacity	89-20 TP37 89-20 TP42	89 x 37 89 x 42	6	32 - 54 32 - 54	810 860
00 pac	Aluminum Platforms ¹				
20 Ca	89-20 EA55	89 x 55	12	32 - 54	715
	Gas Bottle Rack Platform				
	89-20 GBR	89 x 30	12	32 - 54	805

STANDARD, ALUMINUM-FRAME MODELS FOR 96" WIDE BODIES 2


	Model Number	Load Area	Taper	Travel	Gate Weight
1600 lb. Capacity	Aluminum Platforms ¹ A85-16 EA55	85 x 55	12	32 - 54	585
2000 lb. Capacity	Aluminum Platforms ¹ A85-20 EA55	85 x 55	12	32 - 54	585

ADDITIONAL BODY SIZES

Body Size	Model	Load Width
80"	73	73
85"	79	79
90"	85	85
102"	95	95

- 1. See additional aluminum platform depths on page 37.
- Aluminum-Frame Standard Railgate models are sized down due to the accompanying bolt-on mounting flanges. Contact factory for more details.
- **3.** For detailed dimensions, visit **www.tommygate.com**

STANDARD RAILGATE DIMENSIONS 3



STANDARD FEATURES

DOCK **FIXED** FRIENDLY PLATFORM MODELS MODELS

	Recessed Light Kit	•	•
	Safety-trip Bar	•	•
A last	Self-close System	-	•
	Aluminum Sliders	•	•
	Power Cable with Full-length Ground	•	•
	Circuit Breaker	•	•
	Low-profile Control	•	•

- Standard
- Optional
- Not Available

Every pump and motor that goes into any Tommy Gate hydraulic lift must pass an assembly floor test in addition to quality control inspections by the vendor.

AVAILABLE OPTIONS











Above-bed Travel





Dual Controls (w/ pendant)





Taper-integrated Cart Stops





Split Retention Ramps





Rubber Platform Bumpers





Auxiliary Battery Box





PLATFORM MATERIALS





SPLIT CART STOPS

All railgate models with Extruded Aluminum platforms are available with taper-integrated, footactivated, dual cart stops.



SPLIT RETENTION RAMPS

Steel-platforms (standard models 89 & 85 only) are available with add-on retention ramps.




ALUMINUM PLATFORM DEPTHS

Extruded aluminum platforms (on fixed platform models) are available in any depth, 35"-70", in 5" increments. Platforms are comprised of interlocking extrusions of 6061-T6 aircraft-quality aluminum.



GAS BOTTLE RACK PLATFORM

GBR - 30" Loading Depth









G2 SERIES

☆ 1300 - 2000 LBS CAPACITY

MORE THAN A PICKUP LIFT

The Tommy Gate G2 Series is a dual-cylinder, parallel-arm design which utilizes a pair of hydraulic cylinders to lower and raise the lift by applying direct power to both sides of the platform. Supporting larger platforms, G2 Series models are compatible with flatbed, stake and van bodies and offer a wide selection of platform materials to accommodate almost any industry application.

G2-92-1650 TP41

Shown with discontinued recessed light kit. Recessed lights have been replaced by bolt-on kits.



The G2 Series features only two grease points and the hard-chrome pins are virtually maintenance free.

Hydraulic cylinders are built in-house, precision cylinder welds are executed robotically, and assembly and testing are done by hand.





G2 SERIES LIFTGATE FEATURES

- Dual hydraulic cylinders
- Virtually maintenance-free components
- Recessed control
- Hitch compatibility
- Larger platforms
- Fully-enclosed hydraulic system located within the liftgate mainframe





MODELS FOR 96" WIDE BODIES

TWO-YEAR STANDARD WARRANTY

	Model Number	Load Area	Taper	Travel	Platform Fold	Gate Weight
	Treadplate Platforms					
1300 lb. Capacity	G2-92-1350 TP35	87 x 35	6	50	No	628
	G2-92-1350 TP41	87 x 41	6	50	No	655
	<u>TommyTraction™ Platform</u>					
	G2-92-1350 TT33	87 x 33	6	50	No	612
30(apa	Aluminum Platforms					
≌ చ	G2-92-1350 EA37	85 x 37	6	50	No	561
	G2-92-1350 EA41	85 x 41	6	50	No	577
	Bar Grate Platform					
	G2-92-1350 BG33	87 x 33	6	50	No	637
	<u>Treadplate Platforms</u>					
1600 lb. Capacity	G2-92-1650 TP35	87 x 35	6	50	No	628
	G2-92-1650 TP41	87 x 41	6	50	No	655
	<u>TommyTraction™ Platform</u>					
	G2-92-1650 TT33	87 x 33	6	50	No	612
	<u>Aluminum Platforms</u>					
	G2-92-1650 EA37	85 x 37	6	50	No	561
	G2-92-1650 EA41	85 x 41	6	50	No	577
	Bar Grate Platform					
	G2-92-1650 BG33	87 x 33	6	50	No	637
			1			
	<u>Treadplate Platforms</u>					
<u>ج</u> به	G2-92-2050 TP35	87 x 35	6	50	No	644
aci	G2-92-2050 TP41	87 x 41	6	50	No	680
2000 lb. Capacity	<u>Aluminum Platforms</u>					
70	G2-92-2050 EA37	85 x 37	6	50	No	563
	G2-92-2050 EA41	85 x 41	6	50	No	577
1074	POFILE MODELS					
LOW-PI	ROFILE MODELS		r	Γ	I	
<u>خ</u> نه	<u>Treadplate Platforms</u>					
0 II	G2-92-1642 TP38	85 x 38	4	42	YES	609
1600 lb. Capacity	<u>Aluminum Platforms</u>					
0	G2-92-1642 EA38	85 x 38	6	42	YES	523

ADDITIONAL BODY SIZES

Body Size	Model	Load Width
90"	87	80
85"	81	75
80"	73	66
> 67"	65	60

1. For detailed dimensions, visit www.tommygate.com

G2 SERIES DIMENSIONS 1

